

TECHNICAL DATA				
	Standard	Requirement	Unit	Results
PRODUCT DESCRIPTION				
Thickness	EN ISO 24346	-	mm	8.0
Width	EN ISO 24341	-	lm	1.5 / 1.8
Length	EN ISO 24341	-	lm	20
Weight	EN ISO 23997	-	kg/m ²	5.7
SPORT CHARACTERISTICS				
Shock absorption	EN 14808	≥ 25	%	≥ 35
Sliding coefficient	EN 13036-4	80 - 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
Vertical deformation	EN 14809	≤ 3.5	mm	≤ 3.5
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥ 8
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
Impact sound insulation	EN ISO 717-2	-	dB	28
CLASSIFICATION				
Fire rating	EN 13501-1	-	-	Cfl-s1
Anti-bacterial activity	ISO 22196	-	-	Good
DECLARATION OF PERFORMANCE				
CE	DOP-005-1037-A	-	-	Fire Shock Absorption Sliding Coefficient Abrasion Resistance Rolling Load Resistance

* For different roll length, please contact us.